


# BOLT 120



### AVAILABLE BLADES



### TECHNICAL CHARACTERISTICS



### ACCESSORIES



### PACKAGE



- For cutting porcelain, single-double fired, marble and granite.
- Maximum length of cut 120 cm (47 1/4").
- Maximum depth of cut 55 mm (2 1/8") in single pass; 65 mm (2 1/2") in double pass.
- Diamond blade Ø 250 mm (10").
- Plunge cut and adjustable cutting depth.
- Heavy Duty water pump. High capacity double jet water cooling.
- Sliding bar, pivots and disc cover in aluminum.
- Easy-to-remove aluminum work benches for easy cleaning and maximum sturdiness.
- Coated metal frame.
- Re-adjustable aluminum square.

- Motor moves on 4 polypropylene pulleys.; each pulley is reinforced with 2 inside bearings.
- Pulleys are easy to re-adjust (tighten): avoid play and confer long lasting precision of cut.
- Motor held by galvanized metal frame.
- Tiling legs.
- Tilting movement (0-47°) for 45° angle cut (jolly).
- Available accessories: extra side square, self-standing side bench with rollers, 4 wheels + 2 handles kit, wheel feed kit.
- Supplied with Ø 250 mm (10") diamond disc for porcelain tiles, user manual, keys kit, dressing stone.

### MODEL SPECIFICATIONS

Part No.	Barcode	Box	Lightning Bolt	M	Motor	Motor	Blade	Blade	
<b>225MS 120EU</b>	8024648088673	1	230 V 50 Hz	Single-phase	1,5 HP / 1,1 kW	2800	250 mm	10"	2800
<b>225MS 120BR</b>	8024648089755	1	230 V 60 Hz	Single-phase	1,5 HP / 1,1 kW	3360	250 mm	10"	3360
<b>225MS 120US</b>	8024648089779	1	110 V 60 Hz	Single-phase	1,5 HP / 1,1 kW	3360	250 mm	10"	3360
<b>225MS 120GB</b>	8024648089762	1	110 V 50 Hz	Single-phase	1,5 HP / 1,1 kW	2800	250 mm	10"	2800

### CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS / WEIGHT

Model	Blade Diameter	Blade Thickness	Blade Depth	Length	Width	Height	Weight	Case Dimensions	Case Weight	
<b>BOLT 120</b>	250 mm 10"	55 mm 2 1/8"	30 mm 1 3/16"	120 cm 47 1/4"	∞	85x85 cm 33 1/2"x33 1/2"	150x56x h50 cm 59"x22"x h19 5/8"	50 Kg 110.2 lbs	165x65xh 55 cm 65"x25 1/2"xh21 5/8"	66 Kg 145.5 lbs

