











## AVAILABLE BLADES





























TECHNICAL CHARACTERISTICS




























- Maximum length of cut 90 cm (35 1/2").
- Maximum depth of cut 100 mm (4") in single pass; 135 mm (5 1/3") in double pass.
- Diamond blade max Ø 350 mm (14"); min Ø 300 mm (12").
- Plunge cut and adjustable cutting depth.
- Heavy Duty water pump. High capacity double jet water cooling.
- Sliding bar and disc cover in aluminum.
- Easy-to-remove aluminum work benches for easy cleaning and maximum sturdiness.
- Coated metal frame.
- Re-adjustable aluminum square.
- Motor moves on 4 polypropylene pulleys; each pulley is reinforced with 2 inside bearings.

- Pulleys are easy to re-adjust (tighten): avoid play and confer long lasting precision of cut.
- Motor assembly holder and pivots in galvanized steel.
- Tiling legs.
- Tilting movement (0-47°) for 45° angle cut (jolly).
- $\bullet$  Available accessories: extra side square, self-standing side bench with rollers , 4 wheels + 2
- Supplied with Ø 350 mm (14") diamond disc for porcelain tiles, user manual, keys kit, dressing stone.

## MODEL SPECIFICATIONS

MODEL SI EGITORIS										
Part No.			M	M			•			
224MS 90EU	8024648088611	1	230V 50 Hz	Single-phase	3 HP / 2,2 kW	2800	300 mm 12"	2800		
224MS 90BR	8024648090492	1	230V 60 Hz	Single-phase	3 HP / 2,2 kW	3360	300 mm 12"	3360		
224MS QUIIS	8024648090508	1	110V AO H <sub>7</sub>	Single-phase	2 HP / 1 5 kW	3360	300 mm 12"	3360		

CUITING SPECIFICATIO	S SPECIFICATIONS AND MACHINE DIMENSIONS / WEIGHT												
Model	+ + +												
MISTRAL 90	350 mm 300 mm	14" 12"	100 mm 60 mm	4" 2 3/8"	60 mm 45 mm	2 3/8"	90 cm 35 1//	∞	63x63 cm 25"x25"	120x60x h60 cm 47 14"x23 58"x h23 58"	60 Kg 132 3 lbs	130x58x h72 cm 51 1/8"x22 3/4"x h 28 3/8"	70 Kg 154 3 lbs

